Technical description





Technical description

1. Dimensions / Weight



	Dimensions (mm)										Weight				
Model	Α	В	С	D	E	F	G	Н	J	к	L	ı	М	N	(kg)
WITHME P PRF	420-540	455	475	480	980-1100	460	445	560	710	_	645	_	_	_	10,3

A - Seat heightB - Seat depth C - Seat surface depth ${\bf D}$ - Seat width E - Overall height

F - Backrest width **G** – Backrest length H - Backrest height J - Base diameter K - Base width

L - Overall depthI - Headrest height (above the backrest)

M - Headrest width N - Headrest height

	Dimensions (mm)								
Model	Z	Υ	x	w	V	Weight (kg)			
ARF	245	215	68	490	626	_			

Z – Armrest height **Y** – Armrest length

X – Armrest width

W- Internal width between armrests

V - External width between armrests

Technical description

2. Materials / Versions

2.1. Base

Bases:

- Ø 710 mm five-star black polyamide (TS36),
- Ø 710 mm five-star light grey polyamide
- Ø 710 mm five-star polished aluminium (ST64-POL).

2.2. Castors

Ø 60 mm black plastic self-braking castors for soft floors (ESH60) as standard, or hard floors (ESHH60) as an option.

Ø 60 mm light grey plastic self-braking castors for soft floors (ESH60-G) or hard floors (ESHH60-G), both as an option.

2.3. Mechanisms

Self-tension mechanism with automatic weight adjustment (ME-WM) – an innovative mechanism that uses flexible properties of plastics used, ensuring synchronous and smooth movement of seat and backrest.

Functions:

- free-floating synchronous backrest and seat
- backrest tilt angle of 24° synchronised with the seat tilt angle of 5°,

- backrest block at upright position,
- automatic backrest tilt force adjustment to user's weight,
- smooth height adjustment of the chair with pneumatic gas lift.

2.4. Seat and backrest

Seat

Upholstered seat - structure made of polypropylene (PP) covered with injected foam, thickness 40 mm and density 68 kg/m³. Seat cover, also part of the movement system, is made of black or light grey glass fiber reinforced polyamide (PA + GF).

Backrest

Perforated plastic backrest - made of black or light grey polyamide reinforced with glass balls (PA + GB), contoured on the entire surface. <u>Upholstered backrest pad</u> – made of Runner 3D fabric, available as an option.

3. Armrests

Fixed armrests - armrest bar made of black or light grey glass fiber reinforced polyamide (PA + GF), armrest pad made of black or dark grey polypropylene (PP).

4. Assembly / Packaging

Chair partially assembled, L-shape cardboard packaging (PACK-L), 1 piece per box, 6 pieces on pallet - as standard.

The cardbox contains 3 elements:

- seat with assembled mechanism, backrest and armrests.
- base with assembled castors,
- gas lif.

Chair partially assembled, compact cardboard packaging (dimensions suitable for courier delivery – PACK-A1), 1 piece per box, 8 pieces on pallet - as an option.

The cardbox contains:

- seat with assembled mechanism and armrests.
- backrest,
- base with assembled castors,
- gas lift.

Chair assembled, cardboard packaging (PACK-ASM), 1 piece per box, 4 pieces on pallet

5. Technical regulations, approvals and quality marks for the chairs (for selected product configurations)

- GS safety certificate (pending),
- Ergonomics tested (pending).