

VELVET

Arch. Giorgio Topan / 2018



① Shell

Curved beech / birch plywood, 13 mm thickness - padding in polyurethane foam ECOELAST 30, density 30 kg/m³ or on request padding in fire retardant polyurethane foam T 40/P CM, density 40 kg/m³ (C.S.E. RF 4/83 (UNI 9175) test method) class 1 IM.

② Backrest

Structural rigid polyurethane in high density (ideale for the production of articles with variable thickness), high mechanical and shock resistant, undeformable, average density 600 kg/m³, fire retardant meets the requirements class B (DIN 4102) - padding in fire retardant polyurethane foam T 40/P CM, density 40 kg/m³ (C.S.E. RF 4/83 (UNI 9175) test method) class 1 IM - backrest blade in steel from 8 mm thickness.

③ Armrests

Fixed: aluminium alloy EN AB 44100, cast in shell, powder coated matt black or polished - backrest blade in steel, 6 mm thickness, painted in chrome effect RAL 9006.

Fixed Padded: insert in aluminium alloy EN AB 44100 - padding in fire retardant polyurethane foam T 40/P CM, density 40 kg/m³ (C.S.E. RF 4/83 (UNI 9175) test method) class 1 IM - armrest blade in steel, 6 mm thickness, painted in chrome effect RAL 9006.

3D Adjustable: in black nylon - height adjustable armrest in 100 mm stroke - 360° rotation pad - forward and backward adjustable pad in 40 mm stroke - pad in black soft polyurethane.

④ Seat

Padding in fire retardant polyurethane foam T 40/P CM, density 40 kg/m³ (C.S.E. RF 4/83 (UNI 9175) test method) class 1 IM, average thickness 50 mm with insert in polypropylene.

⑤ Mechanisms

Conetto: body in aluminum alloy, painted with epoxy paint.

Weight activated, synchronized mechanism with seat connection integrated and height adjustment seat from integrated lever. Tilt angle: 2° seat and 18° backrest with integrated lever for lock/unlock in 3 positions with antishock device - tension fine tuning by provided hex key for adjust the chair comfort, meets the requirements ANSI-BIFMA X5.1-2017 and UNI EN 1335-3:2009.

⑥ Columns

Gas: steel painted black or chromed, meets the requirements EN16955:2017 CLASSE 4.

Swivel: body in reinforced nylon with steel pin for Ø 28 mm cone.

Swivel: body in steel painted black with epoxy paint Ø 50 mm H 120 mm with galvanized steel pin Ø 28 mm.

VELVET - DTEC - EN - 04-08 -2020



Diemme.

VELVET

Arch. Giorgio Topan / 2018



⑦ Bases

4 Star base: in natural ash wood painted with swivel in aluminium alloy for Ø 28 mm cone.

4 Star base: in black aluminium painted or polished Ø 700 mm, meets the requirements ANSI-BIFMA X5.1-2011 and LGA2830-22AP.

4 Star base: in black aluminium painted Ø 820 mm, meets the requirements ANSI-BIFMA X5.1-2011.

5 Star base std: in polished aluminium Ø 680 mm, meets the requirements ANSI-BIFMA X5.1-2011 and LGA 2830-22AP.

5 Star base design: in black painted or polished aluminium Ø 700 mm, meets the requirements ANSI-BIFMA X5.1-2011, LGA 2830-22AP and LGA2830-22AR.

⑧ Castors and Glides

Self-braking swivel castors for hard floors Ø 65, shock-resistant and wear-resistant "W" type, meets the requirements ANSI-BIFMA X5.1-2011/17 and DIN EN 12529.

⑨ Optional

Headrest padding in polyurethane foam 35 PF FR, density 35 kg/m³ or on request in fire retardant polyurethane foam T 40/P CM, density 40 kg/m³ (C.S.E. RF 4/83 (UNI 9175) test method) class 1 IM

Upholstery

Flame-retardant class 1, flame-retardant or fire-retardant coated fabric, real European leather.

See cover folder with a wide selection of colors and materials.

On request the product is made with customer fabric/leather.

Packaging

Reinforced cardboard box - nylon bag for block chair - loose base - nylon bag for wheels and gas lift.

Instruction and maintenance booklet.


Certifications

UNI EN 1335 type C.


CLASS 1 IM Italian certificate.

VELVET


Arch. Giorgio Topan / 2018




5 star base w/syncron - Presidential




5 star base w/syncron and armrests in aluminium Presidential




5 star base w/syncron and armrests padded and upholstered - Presidential




5 star base w/syncron - Executive




5 star base w/syncron and armrests in aluminium Executive




5 star base w/syncron and armrests padded and upholstered - Executive




4 star base swivel




4 star base swivel w/armrests in aluminium




4 star base swivel w/armrests padded and upholstered




4 star wood base swivel




4 star wood base swivel w/armrests in aluminium



4 star wood base swivel w/armrests padded and upholstered



4 star base Lounge w/armrests padded and upholstered



Feetrest 4 star base swivel

VELVET - DTEC - EN - 04-08-2020



Diemme.